



Servolux SX series

The Servolux **SX-26**, **SX-40** and **SX-55** series is Fireco product made in Italy, meant for emergency lighting when power source is not available. They can grant with a great autonomy with very low weight, easy carry & portable with modular concept. The power supply is from the battery.

Battery

The power is given by a rechargeable 12V with high efficiency battery. With the highest quality **AGM** (**Absorbed Glass Mat**) technology, this battery is acid emission-free, non-spill able and requires no maintenance because they are sealed. Each single cell of the battery has a built-in unidirectional security valve in order to prevent gas overpressure due to misuse. A **corrosion resistant portable metallic battery base** (especially important for patrol boat in sea fog condition) and the plastic molded cover is completing the battery container. On the upper part there is a weather proof socket allowing the floodlight or other compatible devices feeding as well as to recharge the battery. A battery charger will be provided, which is more effective in terms of charging time and much more compact compared to others, mainly for portable application. With **battery indicator**, indicating battery level.

Pneumatic Telescopic mast

The pneumatic telescopic mast is made by **fully anodized Aluminium light alloy**, which is corrosion proof, with **3 sections** and the **main tube is Ø52mm**. It is equipped with **innovative "Twin Lock" system** in order to stop the mast at any height, manually turn the light 360°, and prevent turning when subjected to strong wind. The mast is fixed on the unit by a fixed joint at the bottom and by spring clamping fit on a metallic holder, allowing an easy and quick mounting and disassembly.

The mast is manually extendable / retractable and it has an **air cushion amortizing a possible fast extension or retraction** of the section and therefore does not damage the floodlight. The mast completely retracted is 967mm, **complete system extended is 2500mm**. There is a seat on mast top to fit the floodlight.


Floodlight


LED floodlight of 50W (8,800 lumens) or 80W (12,320 lumens), 12V, is weatherproof with IP66 rating, and has a lifetime of 100,000 hours. At 1.1kg, it is lightweight and portable.











*Drawing for reference, actual dimensions may vary

Ref.	Battery capacity (Ah)	Autonomy (Hours)	Lamp type	Total system extended height (mm)	Mast retracted height (mm)	Weight (kg)
SX-26	26	>4 hours (if fully charged)	50W or 80W LED IP66	2500	967	18

Ref.	Battery capacity (Ah)	Autonomy (Hours)	Lamp type	Total system extended height (mm)	Mast retracted height (mm)	Weight (kg)
SX-40	40	>6 hours (if fully charged)	50W or 80W LED IP66	2500	967	26

Ref.	Battery capacity (Ah)	Autonomy (Hours)	Lamp type	Total system extended height (mm)	Mast retracted height (mm)	Weight (kg)
SX-55	55	>8 hours (if fully charged)	50W or 80W LED IP66	2500	967	28.5



CODES FOR ORDERING

10.621 = Portable base with mast holder SX 26

10.622 = Portable base with mast holder SX 40

10.623 = Portable base with mast holder SX 55

10.606 = Mast Ø52 - 3 sections

ACCESSORIES



	WorkLED LZ 50W	WorkLED LZ 80W	
	Code : 10.631	Code : 10.637	
Power	50W	80W	
Lumens	8800 LM	12320 LM	
Voltage	12-40 VDC	12-40 VDC	
IP Protection	IP 66	IP 66	
Dimensions	128 x 148 x 70 mm	128 x 148 x 70 mm	
Weight	1.1 Kg	1.1 Kg	







10.620

10.624

10.625

Battery charger 12V/230V 10A/h

 $\rm n^{\circ}$ 4 Stabilizing feet adjustable in height $\,$ Battery charger 12V/230V 4A/h for SX26

for SX40 and SX55







Key features:

1. Pneumatic Telescopic Mast



- Fully anodized Aluminium alloy, providing corrosion proof in sea fog condition when using on sea patrol boat.
- 3 sections tubes with main tube diameter of 52mm, providing sturdy and stable deployment.
- Innovative "Twin Lock" system, enables extension and stop at any height, and prevent turning when subjected to strong wind.
- Manual turnable 360°, provide full illumination coverage.
- With air cushion, amortizing a possible fast extension or retraction of the section and therefore does not damage the floodlight.
- Mast top with slot for fitting of lamp unit.

2. Battery Pack



- 12V high efficiency rechargeable battery.
- AGM (Absorbed Glass Mat) technology, battery is acid emission-free, sealed, non-spillable, requires no maintenance and no leakage.
- Each single cell of the battery has a built-in unidirectional security valve in order to prevent gas overpressure due to misuse.
- Corrosion resistant portable metallic battery base with a light weight plastic moulded cover, especially important for patrol boat in sea fog condition.
- With battery level indicator.
- With clamp and strap for better and easy securing of the mast and easy dismantle.

3. Intelligent Battery Charger



This is an intelligent Compact Battery Charger for charging the battery

The charger has LCD display that shows:

- Battery charging status,
- Setting of the charger
- Codes of any anomalies and test results